

PS-105 PARCEL SCALE

Features

- Design for shipping/warehouse applications
- Powder painted mild steel understructure with stainless steel platform
- Equipped with single point load cell
- Stainless steel housing EHI-B indicator
- LCD display with optional blue backlight
- With wall bracket and optional desk mount
- Hold function for convenience of weight reading
- 3m coil style loadcell cable for durability and easy extension
- With RS232 interface to communicate with PC



Specifications

Item	Parameters		
Capacity	30kgx0.005kg / 66lbx0.01lb	60kgx0.01kg / 130lbx0.02lb	120kgx0.02kg / 250lbx0.05lb
Units of Measure	kg, lb, lb:oz		
Display	5½ digits 0.65" high LCD display with optional blue backlight		
Function Keys	UNIT, TARE, ON/OFF/ZERO		
Serial Port	standard bi-directional full duplex RS232		
Power	6VDC 500mA adapter with center positive (included) or 4xAAA batteries (not included)		
Operation Temp	-10°C to 40°C (14°F to 104°F)		
Platform	305mm(L)x305mm(W)x75mm(H) / 12"(L)x12"(W)x3"(H)		
Packing	55x55x40cm/6pcs/ctn	G.W.: 26kg N.W.: 24kg	
	20' container can hold 1338pcs		40' container can hold 2876pcs
Approvals	CE and WEEE directive, UL/CE/BS approved power adapter		
Options	RS232 cable, desk bracket, backlight		